















Cable fasteners (along rail base) for SBBI, INOX V4A.	45.I		
Cable fastener (along rail base) for UIC54E/SBBIV, INOX V4A, light design. (without illustration: for UIC60/SBBVI).	45.IVL (45.VIL)		
Cable fastener (along rail base) for UIC54E/SBBIV, INOX V4A, solid design. (without illustration: for UIC60/SBBVI).	45.IVS (45.VIS)		
Pipe fastener (on wood and steel sleepers), for PE pipe large*. Mounting with Multi-Monti screws recommended.	47GKV		386.79.724
Pipe fastener (on wood, steel, concrete sleepers), for PE pipe small*. Mounting with Multi-Monti screws recommended.	42KBV		386.79.721
Pipe fastener (on wood, steel, concrete sleepers), for PE pipe large*. Mounting with Multi-Monti screws recommended.	42GKV		386.79.722
Pipe fastener (on wood, steel, concrete sleepers), for PE pipe large*, reinforced design. Mounting with Multi-Monti screws recommended.	42GKBV		
Pipe socket for PE pipe small*, for dilatations on all types of sleeper (wood, steel, concrete).	49K		
Z holder for PE pipe small*, for steel & two-block concrete sleepers as well as protective rails.	48K (48GK)		386.79.725 (386.79.726)
Polyethylene (PE) protective cable pipe small*, soft, black, 0.24 kg/m, length 5 m. (without illustration: PE pipe large*).	38KR (40KR)		386.63.809 (453.60.312)
Cable clip, INOX, single lapping, for ø 7.0 until 9.5 mm. Mounting with Multi-Monti screws or nail dowels recommended. (Without illustration: for ø 10 to 13 mm).	38KBE7 (38KBE10)		
Cable clip, INOX, double lapping, solid design, for PE pipe large*. (Without illustration: light design / for PE pipe small* / for wires ø 8 / ø 11 mm).	38KB (40KBI / 40KBs / 38KB8 / 38KB11)		386.79.723
KAGO track box, for easy access to your electrical rail connections even when track is covered! Hot-dip galvanized, available for various rail profiles.	35KV		NEW: Also for screwed fixing!
Multi-Monti screw for all types of sleeper, yellow plated, no spreading pressure , ø 7.5 x 35 mm, bore ø 6 mm (wood, concrete) or 6.5 mm (steel). Also in other dimensions and coatings available.	230KGP		
Nail dowel, INOX V2A, ø 6 x 40 mm. Not appropriate on sleepers. (also in other dimensions & coatings available).	245K	