




KAGO cables

	<u>KAGO-No.</u>		<u>Article-No.</u>
Copper rope, 50 mm ² cross-section, structure: 7x7x1.14mm, Ø _{ext.} ≈ 10.0mm, semi-rigid, bare.	50CUBHS		201010.020
Copper rope, 95 mm ² cross-section, structure: 19x2.52mm, Ø _{ext.} ≈ 12.6mm, rigid, bare.	95CUBS		201010.030
Copper cable, 50 mm ² cross-section, structure: ≈ 19x1.8mm, Ø _{ext.} ≈ 11.2mm, stiff, insulation yellow-green, halogen-free, UV proof.	50CUIGGShfuv		201025.022
Copper cable, 50 mm ² cross-section, structure: ≈ 19x1.8mm, Ø _{ext.} ≈ 11.2mm, stiff, insulation yellow, halogen-free, UV proof.	50CUIGShfuv		201025.026
Copper cable, 50 mm ² cross-section, structure: class 5, flexible, double insulated, insulation yellow-green, coating orange, halogen-free. For crane and building site grounding (without illustration: 95mm ² / 120mm ² / 150mm ²)	50 CUIOEhf (95mm ² / 120mm ² / 150mm ²)		201030.020 (201030.030 / 201030.035 / 201030.040)
Copper cable, 95mm ² cross-section, structure: ca. 19x2.5mm, Ø _{ext.} ≈ 15.3mm, Cu-Ø = 12.6mm, insulation yellow, halogen-free.	95CUIG		201025.043
Copper cable, 25 mm ² cross-section, structure: ca. 200x0.4mm, Ø _{ext.} ≈ 9.0 mm, Cu-Ø = 6.2 mm, insulation black.	25CUISP		201015.010
Copper cable, 50 mm ² cross-section, structure: ca. 400x0.4mm, Ø _{ext.} ≈ 12.5 mm, Cu-Ø = 8.9 mm, insulation black.	50CUISP		201015.020
Copper cable, 70 mm ² cross-section, structure: ca. 356x0.5mm, Ø _{ext.} ≈ 13.9 mm, Cu-Ø = 10.5 mm, insulation black.	70CUISP		201015.025

Further wires, ropes and cables on request!