

KAGO grounding fittings

Grounding set (hot-dip galvanised) for wire mesh fences, length 2.10 m. (Can be shortened itself to: 1.05 m, 1.25 m, 1.55 m, 1.85 m). Delivering without cable lug.

KAGO no.

30KVu



Item no.

615510.045


Pipe post grounding set (34KV, hot-dip galvanised), for pipe diameters 1/2" (21 mm) to 2" (60 mm), solid design. Approved by SBB.



615510.110

Pipe post grounding set (Cu) for 1" pipe or Ø_A 32.7 – 34.7 mm, light design. (without figures: for 3/8" or Ø_A 16.2-18.2mm, 1/2" or Ø_A 20.3 – 22.3mm, 3/4" or Ø_A 25.9 – 27.9 mm)

34.1K (34.3-8K / 34.1-2K / 34.3-4K)



615510.130
(615510.115,
615510.120,
615510.125)

Pipe post grounding set (Cu) universal for 3/8" - 2". (without figure: universal 1 1/2" - 4")

34.3-8-2K
(34.11-2-4K)



615510.200
(615510.210)

Parallel clamp for grounding gabions, Inox A4

PK



615510.060

Grounding clamp for construction equipment at machine or mast end (with screwed connection M12).

EFK



615510.952

Grounding clamp for construction equipment at rail or mast end (with screwed connection M10).

SEK



615510.951

Mast clamp version C for fixing temperature sensors at the rail (Please have a look at the separate flyer and mounting instructions).

34.C



615510.106

Mast clamp M10 with blue marking and with 2 tinned clamping pieces

34.MKb



615510.102

Mast clamp version B for grounding of masts, steel beams (Please have a look at the separate flyer and mounting instructions).

34.B



615510.105