

| | <u>KAGO No.</u> | | <u>Article No.</u> |
|---|-------------------------------------|---|--|
| Grounding block M12 rough for 10 mm wire / 50 mm ² cable. | 256.2Kr |  | 615520.163 |
| Clamping piece copper tinned, with 2 grooves 10mm for 50 mm ² cable. | 256.1Kcz |  | 615520.149 |
| Fittings to grounding block: Screw M12x30 INOX A2 | M12x30V2 |  | 301010.0412 |
| Fittings to grounding block: Spring washer M12 INOX A2 | M12FV2 |  | 304010.0400 |
| Copper Bus Bar 10xM10-M for installation at catenary masts DIL 18-26. Suitable for cable lugs until max. 95mm ² . | ES 10xM10-M |  | 615510.600 |
| Copper Bus Bar 12xM10 incl. two insulators M10. Suitable for cable lugs until max. 95mm ² . (without figures: 6xM10, 6xM12). | ES 12xM10 (ES 6xM10 ES 6xM12) |  | 615510.646 (615510.643 615510.642) |
| Copper Bus Bar 16xM10. Suitable for cable lugs until max. 95mm ² . | ES 16xM10 |  | 615510.640 |
| Copper Bus Bar 2xM10-g for installation on top of grounding block. Suitable for cable lugs until max. 95mm ² . (without figure: Copper Bus Bar 2xM12). | ES 2xM10-g |  | 615510.621 |
| Copper Bus Bar 4xM10-g for installation on top of grounding block or directly on thread in mast. Suitable for cable lugs until max. 95mm ² . | ES 4xM10-g |  | 615510.630 |
| Copper Bus Bar 6xM10-g for installation on top of grounding block or directly on thread in mast. Suitable for cable lugs until max. 95mm ² . | ES 6xM10-g |  | 615510.635 |