

KAGO welding and screwing fittings

Copper screwing rail connector, straight, 50 mm² cross-section, cable length and cable lugs according to customer's requirements. (without illustration: insulated connectors black, transparent, yellow and yellow-green with shrinking tubes)

Article No.

div.




Copper welding rail connector, type U or L, 50 mm² cross-section, cable length according to customer's requirements.

div.



Rail connection M10 Cembre, for rail web 14-16.5mm (without illustration: also for rail web 11-14mm)

611020.010
(611020.011)



Rail connection M12 Contec, simple as well as double connection M12

611026.110



DIN Cable lug M10 for 50 mm² cross-section

(without illustration: 35mm² / 70mm² / 95mm² / 120mm² / 150mm² / 185mm² / 240mm² / 300mm²)

div.



DIN Cable lug M12 for 70 mm² cross-section


(without illustration: 35mm² / 50mm² / 95mm² / 120mm² / 150mm² / 185mm² / 240mm² / 300mm²)

div.



Heat shrink tubes with glue, black or transparent, standard, length 50mm (for Cable lugs 16-95mm²) and 70mm (for cable lugs 120-240mm²)

627010.020 black small
 627010.022 black big
 627010.010 transp. small
 627010.012 transp. big



Heat shrink tube, not gluey, at a stretch, yellow, for cable lugs 16-95 mm² (without illustration: for cable lugs 120-240mm²)

627010.130
(627010.135)



Heat shrink tubes, per meter, with glue, black, yellow-green or transparent, for cable lugs 16-95 mm²

